



RECOMMENDED APPLICATIONS

EXTRUDED POLYSTYRENE BOARDS STYRODUR® C

Styrodur® C

provided by

D-BASF
The Chemical Company

Styrodur® C	2500 C	2800 C	3035 CS	3035 CN	4000 CS	5000 CS
Load Bering floor slabs ¹⁾			■		■	■
Domestic floors	■	■	■			
Load Bering floors	■	■	■		■	■
Perimeter ¹⁾ floor slabs			■		■	■
Perimeter ¹⁾ basement walls			■		■	■
Perimeter ¹⁾ subsoil water areas			■		■	■
Cavity walls	■		■	■		
Internal walls		■				
Lost formwork		■				
Cold bridges		■				
Exterior basement wall insulation		■				
Plaster base		■				
Inverted flat roofs			■		■	■
Duo roofs			■		■	■
Plus roofs			■		■	■
Parking decks					■ ²⁾	■
Promenade roofs			■		■	■
Roof gardens			■		■	■
Conventional flat roofs	■		■		■	■
Parapet walls	■		■			
Pitched roofs	■			■		
Ceilings				■		
Plasterboards laminates		■				
Sandwich panels	■	■				
Warehouses	■		■	■	■	■
Road and railways			■		■	■
Ice rink			■		■	■

1) Insulation in direct contact with the ground

2) not for installation under concrete paving stones

Styrodur® C: Extruded polystyrene foam conforming to DIN EN 13164
Free of CFC, HCFC and HFC

CONTACT

Headquarter: YETICO S.A., ul. Towarowa 17A, 10-416 Olsztyn,
tel. (+4889) 538 78 11, fax (+4889) 538 78 10, e-mail: yetico@yetico.com, www.yetico.com

CUSTOMER SERVICE – OLSZTYN
ul. Towarowa 17A, 10-416 Olsztyn
fax (+4889) 538 78 50
e-mail: bokolsztyn@yetico.com

CUSTOMER SERVICE – GALEWICE
ul. Przemysłowa 5, 98-405 Galewice
fax (+4862) 783 80 22
e-mail: bokgalewice@yetico.com

CUSTOMER SERVICE – GORZÓW WLKP.
ul. Mosiężna 14, 66-400 Gorzów Wielkopolski
fax (+4895) 720 97 30
e-mail: bokgorzow@yetico.com